


Please Approve this Drawing	
Date	
Signature	

NO.	Part Name	Q'TY	Material	Plated surface
1	Plunger	2	无铅铜	AU 3 U" MIN OVER 50~100 U" NI
2	Barrel	1	无铅铜	AU 3 U" MIN OVER 50~100 U" NI
3	Spring	1	SUS	/
4				



NOTES:

- Electrical
 - .Rated Current & Voltage : DC 12 V ; 1.0A Max.
 - .Contact Resistance: 100 mohm maximum at Working Height(Quiescence)
- Mechanical
 - .Full store: 1.40 mm
 - .Working Store: 1.00 mm
 - .Spring Force: 50gf±20gf at Working Height
 - .Durability:10,000 cycles(minimum)
- Environmental
 - .Operating Temperature: -30°C~+85°C
 - .Humidity Range: 10%RH~90%RH
 - .Salt Spray: 48 Hours
- When the current is greater than 1A then need to increase the time delay circuit(3 second)
- To avoid arcing issue, The adaptor start to power supply after connector mated fully.
- To ensure the best usage,please operate it based on the working height.
- .RoHs&HF compliant product.

DRAWN	Kevin	DATE	2021.06.25			东莞市樂瑞电子科技有限公司			
CHECKED		SCALE	10:1	VER.	B.0				
APPROVED		TITLE	pogo pin			Ang:		Dim:	
PROJECT		DRAWING NO.	NC3500-01PA			0	±1°	0	±0.15
SHEET	1 of 1	UNIT	mm			.0	±0.5°	.0	±0.10
						.00	±0.25°	.00	±0.05

VER.	DESCRIPTION	ECN NO.	DATE